

GENERAL EQUIPEMENT FOR FIRST 50 CARBON tall rig

I : 20.03 m
J : 5.36 m
P : 19.50 m
E : 6.50 m

Tapered carbon Sparcraft section 290TR , T 700 fiber, total length 23370mm,
Tube weight 165 kg aprox..
White paint (optional colour available)
Ronstan RC 1260 track (without cars) on aft face
Carbon fiber mast head with 4 sheave (2 aft, 2 spin sheave)
2 spin spectacles above forstay
Carbon fiber two sheave box for jib
Topping lift sheave box
3 tapered aluminium set of spreaders with rod rigging end fittings, 20° swept back
3 aluminium spreader bars for diagonals attachment
6 protected halyards exit
Carbon fiber gooseneck attachment with reef tack fittings
Carbon fiber fitting attachment for hydraulic vang
Mast foot for hydraulic mast jack (with bar)
Electrical internal conduit
Mast collar with shocks, internal water tight and skirt
Sparcraft spi pole track lg 2500 with 2/1 purchase
Mast head light, steaming and deck combined light
windex
3 composite mast steps

MAX DEPTH ALUMINIUM BOOM (idem S version)

Aluminium Sparcraft section with tapered forward end
White paint
Aft sheave box for reef lines and outhaul (4 sheaves)
Tackle for hydraulic vang
4/1 outhaul internal purchase
3 reef lines

ROD STANDING RIGGING

Sparcraft rod rigging
Discontinious type, rod turnbuckles